

Coil Springs Direct



Dimensions and load details are nominal.

Please note that in some cases compression springs will not compress solid without a permanent reduction in free length.

Direction of coiling may be right or left hand.

All stock springs are supplied lightly oiled, other finishes can be supplied on request.

Stock Code No	Outside Diameter	Free Length	Wire Dia	Rate	Approx Solid Height	Approx No Of Coils	Outside Diameter	Free Length	Wire Dia	Rate	Approx Solid Height
	INS	INS	INS	LB/INS	INS		MM	MM	MM	N/MM	MM
S201	0.125	0.500	0.020	20.00	0.240	12.00	3.175	12.70	0.508	3.50	6.12
S202	0.125	0.750	0.020	16.00	0.300	15.00	3.175	19.00	0.508	2.80	7.65
S203	0.125	1.000	0.020	10.50	0.400	20.00	3.175	25.40	0.508	1.84	10.20
S204	0.125	1.250	0.020	9.00	0.480	24.00	3.175	31.80	0.508	1.58	12.24
S205	0.188	0.500	0.022	11.50	0.180	8.00	4.775	12.70	0.559	2.01	4.48
S206	0.188	0.750	0.022	9.00	0.220	10.00	4.775	19.00	0.559	1.58	5.60
S207	0.188	1.000	0.022	7.00	0.280	12.50	4.775	25.40	0.559	1.23	7.00
S208	0.188	1.250	0.022	5.50	0.350	15.50	4.775	31.80	0.559	0.96	8.68
S209	0.250	0.500	0.024	8.00	0.170	7.00	6.350	12.70	0.610	1.40	4.27
S210	0.250	0.500	0.032	29.00	0.230	7.00	6.350	12.70	0.813	5.08	5.67
S211	0.250	0.500	0.040	78.00	0.280	7.00	6.350	12.70	1.016	13.66	7.14
S212	0.250	0.750	0.024	5.50	0.220	9.00	6.350	19.00	0.610	0.96	5.49
S213	0.250	0.750	0.032	21.00	0.290	9.00	6.350	19.00	0.813	3.68	7.29
S214	0.250	0.750	0.040	56.00	0.360	9.00	6.350	19.00	1.016	9.81	9.18
S215	0.250	1.000	0.024	3.75	0.300	12.50	6.350	25.40	0.610	0.66	7.63
S216	0.250	1.000	0.032	11.50	0.450	14.00	6.350	25.40	0.813	2.01	11.34
S217	0.250	1.000	0.040	29.50	0.620	15.50	6.350	25.40	1.016	5.17	15.81
S218	0.250	1.250	0.024	2.75	0.380	15.50	6.350	31.80	0.610	0.48	9.46
S219	0.250	1.250	0.032	9.00	0.560	17.50	6.350	31.80	0.813	1.58	14.18
S220	0.250	1.250	0.040	23.50	0.760	19.00	6.350	31.80	1.016	4.12	19.38
S221	0.250	1.500	0.024	2.50	0.440	18.00	6.350	38.10	0.610	0.44	10.98
S222	0.250	1.500	0.032	7.50	0.660	20.50	6.350	38.10	0.813	1.31	16.61
S223	0.250	1.500	0.040	19.50	0.900	22.50	6.350	38.10	1.016	3.41	22.95
S224	0.250	2.000	0.024	2.00	0.580	24.00	6.350	50.80	0.610	0.35	14.64
S225	0.250	2.000	0.032	5.00	0.870	27.00	6.350	50.80	0.813	0.88	21.87
S226	0.250	2.000	0.040	14.00	1.200	30.00	6.350	50.80	1.016	2.45	30.60
S227	0.313	0.750	0.028	6.50	0.230	8.00	7.950	19.00	0.711	1.14	5.68
S228	0.313	0.750	0.036	18.50	0.290	8.00	7.950	19.00	0.914	3.24	7.28
S229	0.313	0.750	0.048	68.00	0.390	8.00	7.950	19.00	1.219	11.91	9.76
S230	0.313	1.000	0.028	4.75	0.280	10.00	7.950	25.40	0.711	0.83	7.10
S231	0.313	1.000	0.036	12.00	0.420	11.50	7.950	25.40	0.914	2.10	10.47
S232	0.313	1.000	0.048	36.50	0.630	13.00	7.950	25.40	1.219	6.39	15.86

Coil Springs Direct



Dimensions and load details are nominal.

Please note that in some cases compression springs will not compress solid without a permanent reduction in free length.

Direction of coiling may be right or left hand.

All stock springs are supplied lightly oiled, other finishes can be supplied on request.

Stock Code No	Outside Diameter	Free Length	Wire Dia	Rate	Approx Solid Height	Approx No Of Coils	Outside Diameter	Free Length	Wire Dia	Rate	Approx Solid Height
	INS	INS	INS	LB/INS	INS		MM	MM	MM	N/MM	MM
S233	0.313	1.250	0.028	4.00	0.340	12.00	7.950	31.80	0.711	0.70	8.52
S234	0.313	1.250	0.036	10.00	0.490	13.50	7.950	31.80	0.914	1.75	12.29
S235	0.313	1.250	0.048	30.50	0.750	15.50	7.950	31.80	1.219	5.34	18.91
S236	0.313	1.500	0.028	3.25	0.400	14.00	7.950	38.10	0.711	0.57	9.94
S237	0.313	1.500	0.036	8.50	0.580	16.00	7.950	38.10	0.914	1.49	14.56
S238	0.313	1.500	0.048	25.00	0.890	18.50	7.950	38.10	1.219	4.38	22.57
S239	0.313	2.000	0.028	2.25	0.510	18.00	7.950	50.80	0.711	0.39	12.78
S240	0.313	2.000	0.036	6.00	0.760	21.00	7.950	50.80	0.914	1.05	19.11
S241	0.313	2.000	0.048	18.50	1.180	24.50	7.950	50.80	1.219	3.24	29.89
S242	0.313	2.500	0.028	2.00	0.560	20.00	7.950	63.50	0.711	0.35	14.20
S243	0.313	2.500	0.036	6.00	0.720	20.00	7.950	63.50	0.914	1.05	18.20
S244	0.313	2.500	0.048	23.00	0.960	20.00	7.950	63.50	1.219	4.03	24.40
S245	0.375	0.750	0.036	11.00	0.290	8.00	9.525	19.00	0.910	1.93	7.28
S246	0.375	0.750	0.048	36.00	0.390	8.00	9.525	19.00	1.219	6.30	9.76
S247	0.375	0.750	0.064	133.00	0.520	8.00	9.525	19.00	1.626	23.29	13.04
S248	0.375	1.000	0.036	9.50	0.310	8.50	9.525	25.40	0.914	1.66	7.74
S249	0.375	1.000	0.048	27.00	0.480	10.00	9.525	25.40	1.219	4.73	12.20
S250	0.375	1.000	0.064	90.00	0.680	10.50	9.525	25.40	1.626	15.76	17.12
S251	0.375	1.250	0.036	7.25	0.380	10.50	9.525	31.80	0.914	1.27	9.56
S252	0.375	1.250	0.048	22.00	0.580	12.00	9.525	31.80	1.219	3.85	14.64
S253	0.375	1.250	0.064	71.00	0.840	13.00	9.525	31.80	1.626	12.43	21.19
S254	0.375	1.500	0.036	6.00	0.450	12.50	9.525	38.10	0.914	1.05	11.38
S255	0.375	1.500	0.048	17.50	0.700	14.50	9.525	38.10	1.219	3.06	17.69
S256	0.375	1.500	0.064	56.80	1.000	15.50	9.525	38.10	1.626	9.95	25.27
S257	0.375	2.000	0.036	4.50	0.560	15.50	9.530	50.80	0.914	0.79	14.11
S258	0.375	2.000	0.048	13.00	0.890	18.50	9.525	50.80	1.219	2.28	22.57
S259	0.375	2.000	0.064	44.00	1.280	20.00	9.525	50.80	1.626	7.71	32.60
S260	0.375	2.500	0.036	3.50	0.720	20.00	9.525	63.50	0.914	0.61	18.20
S261	0.375	2.500	0.048	12.00	0.960	20.00	9.525	63.50	1.219	2.10	24.40
S262	0.375	2.500	0.064	44.00	1.280	20.00	9.525	63.50	1.626	7.71	32.60
S263	0.438	0.750	0.040	9.50	0.320	8.00	11.125	19.00	1.016	1.66	8.16
S264	0.438	0.750	0.056	42.00	0.450	8.00	11.125	19.00	1.422	7.36	11.36

Coil Springs Direct



Dimensions and load details are nominal.

Please note that in some cases compression springs will not compress solid without a permanent reduction in free length.

Direction of coiling may be right or left hand.

All stock springs are supplied lightly oiled, other finishes can be supplied on request.

Stock Code No	Outside Diameter	Free Length	Wire Dia	Rate	Approx Solid Height	Approx No Of Coils	Outside Diameter	Free Length	Wire Dia	Rate	Approx Solid Height
	INS	INS	INS	LB/INS	INS		MM	MM	MM	N/MM	MM
S265	0.438	0.750	0.072	130.00	0.580	8.00	11.125	19.00	1.829	22.77	14.64
S266	0.438	1.000	0.040	10.80	0.300	7.50	11.125	25.40	1.016	1.89	7.65
S267	0.438	1.000	0.056	37.00	0.510	9.00	11.125	25.40	1.422	6.48	12.78
S268	0.438	1.000	0.072	123.00	0.620	8.50	11.125	25.40	1.829	21.54	15.56
S269	0.438	1.250	0.040	9.25	0.340	8.50	11.125	31.80	1.016	1.62	8.67
S270	0.438	1.250	0.056	28.50	0.620	11.00	11.125	31.80	1.422	4.99	15.62
S271	0.438	1.250	0.072	88.00	0.800	11.00	11.125	31.80	1.829	15.41	20.13
S272	0.438	1.500	0.040	7.50	0.380	9.50	11.125	38.10	1.016	1.31	9.69
S273	0.438	1.500	0.056	23.00	0.730	13.00	11.125	38.10	1.422	4.03	18.46
S274	0.438	1.500	0.072	70.00	0.980	13.50	11.125	38.10	1.829	12.26	24.71
S275	0.438	2.000	0.040	5.25	0.520	13.00	11.125	50.80	1.016	0.92	13.26
S276	0.438	2.000	0.056	18.00	0.900	16.00	11.125	50.80	1.422	3.15	22.72
S277	0.438	2.000	0.072	51.00	1.230	17.00	11.125	50.80	1.829	8.93	31.11
S278	0.438	2.500	0.040	4.00	0.700	17.50	11.125	63.50	1.016	0.70	17.85
S279	0.438	2.500	0.056	14.50	1.120	20.00	11.125	63.50	1.422	2.54	28.40
S280	0.438	2.500	0.072	40.50	1.550	21.50	11.125	63.50	1.829	7.09	39.35
S281	0.438	3.000	0.040	3.00	0.800	20.00	11.125	76.20	1.016	0.53	20.40
S282	0.438	3.000	0.056	14.50	1.120	20.00	11.125	76.20	1.422	2.54	28.40
S283	0.438	3.000	0.072	44.00	1.440	20.00	11.125	76.20	1.829	7.71	36.60
S284	0.500	0.750	0.048	13.00	0.390	8.00	12.700	19.00	1.219	2.28	9.76
S285	0.500	0.750	0.064	48.50	0.520	8.00	12.700	19.00	1.626	8.49	13.04
S286	0.500	0.750	0.080	130.00	0.640	8.00	12.700	19.00	2.032	22.77	16.24
S287	0.500	1.000	0.048	11.50	0.440	9.00	12.700	25.40	1.219	2.01	10.98
S288	0.500	1.000	0.064	48.00	0.520	8.00	12.700	25.40	1.626	8.41	13.04
S289	0.500	1.000	0.080	158.00	0.560	7.00	12.700	25.40	2.032	27.67	14.21
S290	0.500	1.250	0.048	13.50	0.390	8.00	12.700	31.80	1.219	2.36	9.76
S291	0.500	1.250	0.064	38.00	0.580	9.00	12.700	31.80	1.626	6.65	14.67
S292	0.500	1.250	0.080	105.00	0.800	10.00	12.700	31.80	2.032	18.39	23.00
S293	0.500	1.500	0.048	11.00	0.460	9.50	12.700	38.10	1.219	1.93	11.59
S294	0.500	1.500	0.064	31.00	0.710	11.00	12.700	38.10	1.626	5.43	17.93
S295	0.500	1.500	0.080	80.00	0.960	12.00	12.700	38.10	2.032	14.01	24.36
S296	0.500	2.000	0.048	7.75	0.600	12.50	12.700	50.80	1.219	1.36	15.25

Coil Springs Direct



Dimensions and load details are nominal.

Please note that in some cases compression springs will not compress solid without a permanent reduction in free length.

Direction of coiling may be right or left hand.

All stock springs are supplied lightly oiled, other finishes can be supplied on request.

Stock Code No	Outside Diameter	Free Length	Wire Dia	Rate	Approx Solid Height	Approx No Of Coils	Outside Diameter	Free Length	Wire Dia	Rate	Approx Solid Height
	INS	INS	INS	LB/INS	INS		MM	MM	MM	N/MM	MM
S297	0.500	2.000	0.064	24.00	0.900	14.00	12.700	50.80	1.626	4.20	22.82
S298	0.500	2.000	0.080	59.50	1.240	15.50	12.700	50.80	2.032	10.42	31.47
S299	0.500	2.500	0.048	6.25	0.750	15.50	12.700	63.50	1.219	1.09	18.91
S300	0.500	2.500	0.064	19.00	1.090	17.00	12.700	63.50	1.626	3.33	27.71
S301	0.500	2.500	0.080	47.00	1.520	19.00	12.700	63.50	2.032	8.23	38.57
S302	0.500	3.000	0.048	5.25	0.870	18.00	12.700	76.20	1.219	0.92	21.96
S303	0.500	3.000	0.064	15.80	1.320	20.50	12.700	76.20	1.626	2.77	33.42
S304	0.500	3.000	0.080	38.00	1.840	23.00	12.700	76.20	2.032	6.65	46.69
S305	0.625	1.000	0.056	11.00	0.510	9.00	15.875	25.40	1.422	1.93	12.78
S306	0.625	1.000	0.072	46.00	0.510	7.00	15.875	25.40	1.829	8.06	12.81
S307	0.625	1.000	0.092	170.00	0.560	6.00	15.875	25.40	2.337	29.77	14.04
S308	0.625	1.250	0.056	8.50	0.620	11.00	15.875	31.80	1.422	1.49	15.62
S309	0.625	1.250	0.072	28.50	0.720	10.00	15.875	31.80	1.829	4.99	18.30
S310	0.625	1.250	0.092	112.00	0.740	8.00	15.875	31.80	2.337	19.61	18.72
S311	0.625	1.500	0.056	14.00	0.420	7.50	15.875	38.10	1.422	2.45	10.65
S312	0.625	1.500	0.072	35.00	0.620	8.50	15.875	38.10	1.829	6.13	15.56
S313	0.625	1.500	0.092	85.00	0.920	10.00	15.875	38.10	2.340	14.89	23.40
S314	0.625	2.000	0.056	9.50	0.560	10.00	15.875	50.80	1.422	1.66	14.20
S315	0.625	2.000	0.072	25.60	0.800	11.00	15.875	50.80	1.829	4.48	20.13
S316	0.625	2.000	0.092	64.00	1.150	12.50	15.875	50.80	2.337	11.21	29.25
S317	0.625	2.500	0.056	7.75	0.680	12.00	15.875	63.50	1.422	1.36	17.04
S318	0.625	2.500	0.072	19.50	0.970	13.50	15.875	63.50	1.829	3.41	24.71
S319	0.625	2.500	0.092	50.00	1.430	15.50	15.875	63.50	2.337	8.76	36.27
S320	0.625	3.000	0.056	6.00	0.820	14.50	15.875	76.20	1.422	1.05	20.59
S321	0.625	3.000	0.072	16.50	1.160	16.00	15.875	76.20	1.829	2.89	29.28
S322	0.625	3.000	0.092	44.00	1.610	17.50	15.875	76.20	2.337	7.71	40.95
S323	0.625	3.500	0.056	5.00	0.930	16.50	15.875	88.90	1.422	0.88	23.43
S324	0.625	3.500	0.072	13.80	1.340	18.50	15.875	88.90	1.829	2.42	33.86
S325	0.625	3.500	0.092	36.50	1.890	20.50	15.875	88.90	2.337	6.39	47.97
S326	0.625	4.000	0.056	4.25	1.120	20.00	15.875	101.60	1.422	0.74	28.40
S327	0.625	4.000	0.072	12.00	1.440	20.00	15.875	101.60	1.829	2.10	36.60
S328	0.625	4.000	0.092	37.50	1.840	20.00	15.875	101.60	2.337	6.57	46.80

Coil Springs Direct



Dimensions and load details are nominal.

Please note that in some cases compression springs will not compress solid without a permanent reduction in free length.

Direction of coiling may be right or left hand.

All stock springs are supplied lightly oiled, other finishes can be supplied on request.

Stock Code No	Outside Diameter	Free Length	Wire Dia	Rate	Approx Solid Height	Approx No Of Coils	Outside Diameter	Free Length	Wire Dia	Rate	Approx Solid Height
	INS	INS	INS	LB/INS	INS		MM	MM	MM	N/MM	MM
S329	0.750	1.000	0.072	31.00	0.440	6.00	19.050	25.40	1.829	5.43	10.98
S330	0.750	1.000	0.092	90.00	0.560	6.00	19.050	25.40	2.337	15.76	14.04
S331	0.750	1.000	0.116	255.00	0.700	6.00	19.050	25.40	2.946	44.66	17.70
S332	0.750	1.500	0.072	16.00	0.720	10.00	19.050	38.10	1.829	2.80	18.30
S333	0.750	1.500	0.092	60.00	0.740	8.00	19.050	38.10	2.337	10.51	18.72
S334	0.750	1.500	0.116	145.00	1.050	9.00	19.050	38.10	2.946	25.39	26.55
S335	0.750	2.000	0.072	19.50	0.620	8.50	19.050	50.80	1.829	3.41	15.56
S336	0.750	2.000	0.092	45.00	0.920	10.00	19.050	50.80	2.337	7.88	23.40
S337	0.750	2.000	0.116	120.00	1.220	10.50	19.050	50.80	2.946	21.02	30.98
S338	0.750	2.500	0.072	14.50	0.760	10.50	19.050	63.50	1.829	2.54	19.22
S339	0.750	2.500	0.092	36.00	1.110	12.00	19.050	63.50	2.337	6.30	28.08
S340	0.750	2.500	0.116	93.00	1.510	13.00	19.050	63.50	2.946	16.29	38.35
S341	0.750	3.000	0.072	12.00	0.900	12.50	19.050	76.20	1.829	2.10	22.88
S342	0.750	3.000	0.092	30.00	1.290	14.00	19.050	76.20	2.337	5.25	32.76
S343	0.750	3.000	0.116	76.00	1.800	15.50	19.050	76.20	2.946	13.31	45.73
S344	0.750	3.500	0.072	10.00	1.050	14.45	19.050	88.90	1.829	1.75	26.54
S345	0.750	3.500	0.092	26.00	1.480	16.00	19.050	88.90	2.337	4.55	37.44
S346	0.750	3.500	0.116	64.00	2.090	18.00	19.050	88.90	2.946	11.21	53.10
S347	0.750	4.000	0.072	8.50	1.190	16.50	19.050	101.60	1.829	1.49	30.20
S348	0.750	4.000	0.092	22.80	1.660	18.00	19.050	101.60	2.337	3.99	42.12
S349	0.750	4.000	0.116	54.00	2.380	20.50	19.050	101.60	2.946	9.46	60.48
S350	0.750	4.500	0.072	6.75	1.440	20.00	19.050	114.30	1.829	1.18	36.60
S351	0.750	4.500	0.092	20.00	1.840	20.00	19.050	114.30	2.337	3.50	46.80
S352	0.750	4.500	0.116	55.00	2.380	20.50	19.050	114.30	2.946	9.63	60.48
S353	0.875	1.500	0.080	14.50	0.800	10.00	22.225	38.10	2.032	2.54	20.30
S354	0.875	1.500	0.104	61.00	0.840	8.00	22.225	38.10	2.642	10.68	21.20
S355	0.875	1.500	0.128	224.00	0.770	6.00	22.225	38.10	3.251	39.23	19.50
S356	0.875	2.000	0.080	20.00	0.600	7.50	22.225	50.80	2.032	3.50	15.23
S357	0.875	2.000	0.104	57.00	0.890	8.50	22.225	50.80	2.642	9.98	22.53
S358	0.875	2.000	0.128	124.00	1.220	9.50	22.225	50.80	3.251	21.72	30.88
S359	0.875	2.500	0.080	16.00	0.720	9.00	22.225	63.50	2.032	2.80	18.27
S360	0.875	2.500	0.104	45.50	1.040	10.00	22.225	63.50	2.642	7.97	26.50

Coil Springs Direct



Dimensions and load details are nominal.

Please note that in some cases compression springs will not compress solid without a permanent reduction in free length.

Direction of coiling may be right or left hand.

All stock springs are supplied lightly oiled, other finishes can be supplied on request.

Stock Code No	Outside Diameter	Free Length	Wire Dia	Rate	Approx Solid Height	Approx No Of Coils	Outside Diameter	Free Length	Wire Dia	Rate	Approx Solid Height
	INS	INS	INS	LB/INS	INS		MM	MM	MM	N/MM	MM
S361	0.875	2.500	0.128	97.00	1.480	11.50	22.225	63.50	3.251	16.99	37.38
S362	0.875	3.000	0.080	13.80	0.840	10.50	22.225	76.20	2.032	2.42	21.32
S363	0.875	3.000	0.104	37.00	1.250	12.00	22.225	76.20	2.642	6.48	31.80
S364	0.875	3.000	0.128	81.00	1.730	13.50	22.225	76.20	3.251	14.19	43.88
S365	0.875	3.500	0.080	11.80	0.960	12.00	22.225	88.90	2.032	2.07	24.36
S366	0.875	3.500	0.104	31.00	1.460	14.00	22.225	88.90	2.642	5.43	37.10
S367	0.875	3.500	0.128	68.50	1.990	15.50	22.225	88.90	3.251	12.00	50.38
S368	0.875	4.000	0.080	10.30	1.080	13.50	22.225	101.60	2.032	1.80	27.41
S369	0.875	4.000	0.104	27.50	1.620	15.50	22.225	101.60	2.642	4.82	41.08
S370	0.875	4.000	0.128	58.00	2.310	18.00	22.225	101.60	3.251	10.16	58.50
S371	0.875	4.500	0.080	6.50	1.600	20.00	22.225	114.30	2.032	1.14	40.60
S372	0.875	4.500	0.104	20.50	2.080	20.00	22.225	114.30	2.642	3.59	53.00
S373	0.875	4.500	0.128	58.00	2.310	18.00	22.225	114.30	3.251	10.16	58.50
S374	0.875	5.000	0.080	6.00	1.760	22.00	22.225	127.00	2.032	1.05	44.66
S375	0.875	5.000	0.104	20.50	2.080	20.00	22.225	127.00	2.642	3.59	53.00
S376	0.875	5.000	0.128	51.50	2.560	20.00	22.225	127.00	3.251	9.02	65.00
S377	1.000	1.500	0.104	40.00	0.840	8.00	25.400	38.10	2.642	7.01	21.20
S378	1.000	1.500	0.128	140.00	0.770	6.00	25.400	38.10	3.251	24.52	19.50
S379	1.000	1.500	0.160	400.00	0.960	6.00	25.400	38.10	4.064	70.05	24.36
S380	1.000	2.000	0.104	33.00	0.940	9.00	25.400	50.80	2.642	5.78	23.85
S381	1.000	2.000	0.128	97.00	1.030	8.00	25.400	50.80	3.251	16.99	26.00
S382	1.000	2.000	0.160	318.00	1.120	7.00	25.400	50.80	4.064	55.69	28.42
S383	1.000	2.500	0.104	36.00	0.890	8.50	25.400	63.50	2.642	6.30	22.53
S384	1.000	2.500	0.128	77.00	1.220	9.50	25.400	63.50	3.251	13.48	30.88
S385	1.000	2.500	0.160	200.00	1.600	10.00	25.400	63.50	4.064	35.03	40.60
S386	1.000	3.000	0.104	29.50	1.040	10.00	25.400	76.20	2.642	5.17	26.50
S387	1.000	3.000	0.128	65.00	1.410	11.00	25.400	76.20	3.251	11.38	35.75
S388	1.000	3.000	0.160	160.00	1.920	12.00	25.400	76.20	4.064	28.02	48.72
S389	1.000	3.500	0.104	25.00	1.200	11.50	25.400	88.90	2.642	4.38	30.48
S390	1.000	3.500	0.128	56.00	1.600	12.50	25.400	88.90	3.251	9.81	40.63
S391	1.000	3.500	0.160	132.00	2.240	14.00	25.400	88.90	4.064	23.12	58.84
S392	1.000	4.000	0.104	21.50	1.360	13.00	25.400	101.60	2.642	3.77	34.45

Coil Springs Direct



Dimensions and load details are nominal.

Please note that in some cases compression springs will not compress solid without a permanent reduction in free length.

Direction of coiling may be right or left hand.

All stock springs are supplied lightly oiled, other finishes can be supplied on request.

Stock Code No	Outside Diameter	Free Length	Wire Dia	Rate	Approx Solid Height	Approx No Of Coils	Outside Diameter	Free Length	Wire Dia	Rate	Approx Solid Height
	INS	INS	INS	LB/INS	INS		MM	MM	MM	N/MM	MM
S393	1.000	4.000	0.128	48.00	1.800	14.00	25.400	101.60	3.251	8.41	45.50
S394	1.000	4.000	0.160	120.00	2.480	15.50	25.400	101.60	4.064	21.02	62.93
S395	1.000	5.000	0.104	17.50	1.620	15.50	25.400	127.00	2.642	3.06	41.08
S396	1.000	5.000	0.128	37.00	2.240	17.50	25.400	127.00	3.251	6.48	56.88
S397	1.000	5.000	0.160	91.00	3.120	19.50	25.400	127.00	4.064	15.94	79.17
S398	1.000	6.000	0.104	13.00	2.080	20.00	25.400	152.40	2.642	2.28	53.00
S399	1.000	6.000	0.128	32.50	2.560	20.00	25.400	152.40	3.251	5.69	65.00
S400	1.000	6.000	0.160	105.00	2.880	18.00	25.400	152.40	4.064	18.39	73.08
S401	1.250	2.000	0.104	16.00	0.940	9.00	31.750	50.80	2.642	2.80	23.85
S402	1.250	2.000	0.128	44.00	1.030	8.00	31.750	50.80	3.251	7.71	26.00
S403	1.250	2.000	0.160	142.00	1.120	7.00	31.750	50.80	4.064	24.87	28.42
S404	1.250	3.000	0.104	14.00	1.040	10.00	31.750	76.20	2.642	2.45	26.50
S405	1.250	3.000	0.128	31.00	1.410	11.00	31.750	76.20	3.251	5.43	35.75
S406	1.250	3.000	0.160	73.00	1.920	12.00	31.750	76.20	4.064	12.78	48.72
S407	1.250	4.000	0.104	7.00	1.880	18.00	31.750	101.60	2.642	1.23	47.70
S408	1.250	4.000	0.128	22.00	1.920	15.00	31.750	101.60	3.251	3.85	48.75
S409	1.250	4.000	0.160	72.00	1.920	12.00	31.750	101.60	4.064	12.61	48.72
S410	1.250	5.000	0.104	6.25	2.080	20.00	31.750	127.00	2.642	1.09	53.00
S411	1.250	5.000	0.128	18.30	2.180	17.00	31.750	127.00	3.251	3.20	55.25
S412	1.250	5.000	0.160	58.00	2.400	15.00	31.750	127.00	4.064	10.16	60.90
S413	1.250	6.000	0.104	5.25	2.500	24.00	31.750	152.40	2.642	0.92	63.60
S414	1.250	6.000	0.128	15.50	2.560	20.00	31.750	152.40	3.251	2.71	65.00
S415	1.250	6.000	0.160	56.00	2.400	15.00	31.750	152.40	4.064	9.81	60.90
S416	1.500	3.000	0.128	18.80	1.280	10.00	38.100	76.20	3.251	3.29	32.50
S417	1.500	3.000	0.160	56.00	1.440	9.00	38.100	76.20	4.064	9.81	36.54
S418	1.500	3.000	0.192	144.00	1.540	8.00	38.100	76.20	4.877	25.22	39.04
S419	1.500	4.000	0.128	11.80	1.920	15.00	38.100	101.60	3.251	2.07	48.75
S420	1.500	4.000	0.160	40.00	1.920	12.00	38.100	101.60	4.064	7.01	48.72
S421	1.500	4.000	0.192	110.00	1.920	10.00	38.100	101.60	4.877	19.26	48.80
S422	1.500	5.000	0.128	10.00	2.310	18.00	38.100	127.00	3.251	1.75	58.50
S423	1.500	5.000	0.160	30.00	2.400	15.00	38.100	127.00	4.064	5.25	60.90
S424	1.500	5.000	0.192	97.00	2.120	11.00	38.100	127.00	4.877	16.99	53.68

Coil Springs Direct



Dimensions and load details are nominal.

Please note that in some cases compression springs will not compress solid without a permanent reduction in free length.

Direction of coiling may be right or left hand.

All stock springs are supplied lightly oiled, other finishes can be supplied on request.

Stock Code No	Outside Diameter	Free Length	Wire Dia	Rate	Approx Solid Height	Approx No Of Coils	Outside Diameter	Free Length	Wire Dia	Rate	Approx Solid Height
	INS	INS	INS	LB/INS	INS		MM	MM	MM	N/MM	MM
S425	1.500	6.000	0.128	8.00	2.820	22.00	38.100	152.40	3.251	1.40	71.50
S426	1.500	6.000	0.160	23.00	3.040	19.00	38.100	152.40	4.064	4.03	77.14
S427	1.500	6.000	0.192	67.00	2.880	15.00	38.100	152.40	4.877	11.73	73.20
S428	2.000	3.000	0.128	7.50	1.280	10.00	50.800	76.20	3.251	1.31	32.50
S429	2.000	3.000	0.160	21.50	1.440	9.00	50.800	76.20	4.064	3.77	36.54
S430	2.000	3.000	0.192	66.50	1.350	7.00	50.800	76.20	4.877	11.65	34.16
S431	2.000	4.000	0.128	4.75	1.920	15.00	50.800	101.60	3.251	0.83	48.75
S432	2.000	4.000	0.160	15.00	1.920	12.00	50.800	101.60	4.064	2.63	48.72
S433	2.000	4.000	0.192	42.00	1.920	10.00	50.800	101.60	4.877	7.36	48.80
S434	2.000	5.000	0.128	3.75	2.310	18.00	50.800	127.00	3.251	0.66	58.50
S435	2.000	5.000	0.160	11.50	2.400	15.00	50.800	127.00	4.064	2.01	60.90
S436	2.000	5.000	0.192	37.00	2.120	11.00	50.800	127.00	4.877	6.48	53.68
S437	2.000	6.000	0.128	3.00	2.820	22.00	50.800	152.40	3.251	0.53	71.50
S438	2.000	6.000	0.160	9.00	3.040	19.00	50.800	152.40	4.060	1.58	77.14
S439	2.000	6.000	0.192	37.00	2.120	11.00	50.800	152.40	4.877	6.48	53.68
S440	2.000	7.000	0.128	2.75	2.950	23.00	50.800	177.80	3.251	0.48	74.75
S441	2.000	7.000	0.160	9.00	3.200	20.00	50.800	177.80	4.064	1.58	81.20
S442	2.000	7.000	0.192	24.00	3.080	16.00	50.800	177.80	4.877	4.20	78.08
S443	2.000	8.000	0.128	2.50	3.200	25.00	50.800	203.20	3.251	0.44	81.25
S444	2.000	8.000	0.160	7.75	3.520	22.00	50.800	203.20	4.064	1.36	89.32
S445	2.000	8.000	0.192	21.00	3.460	18.00	50.800	203.20	4.877	3.68	87.84